

DECLARATION OF PERFORMANCE according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

Nr. RE 820

1. Unique identification code of the product-type:

KÖSTER ECB 2.0

2. Intended use:

Reinforced ethylene copolymer bitumen (ECB) based waterproofing membrane according to EN 13967:2012 Waterproofing membrane as damp proof sheet

3. Manufacturer:

KÖSTER BAUCHEMIE AG Dieselstraße 1 - 10 26607 Aurich

4. System of AVCP:

System 2+

5a. Harmonised standard:

EN 13967:2012

5b. Notified body:

Materialprüfanstalt (MPA) für das Bauwesen,

Beethovenstraße 52 38106 Braunschweig Identification number 0761-CPD



6. Declared performance:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E		
Water tightness			
Method A	≥ 60 kPa watertight		
Method B	≥ 400 kPa watertight		
Tensile characteristics			
Tensile strength	≥ 6 N/mm²		
Elongation at break	≥ 500 %		
Resistance to static loading			
Method A	≥ 20 kg		
Method B	≥ 20 kg		
Resistance to shock loads			
Method A	≥ 900 mm		
Method B	≥ 1500 mm		
Tear continuation resistance	≥ 400 N		
(nail shank)			
Water vapor permeability	μ = 100000		
Resistance to root penetration	passed		
Resistance of the joint seams	≥ 500 N/50 mm		
to shearing	No failure in the		
	overlap		
UV resistance	passed		
Exposure to bitumen	passed		
Exposure to liquid chemicals including water	passed		

The performance of the product according to point 1 and 2 corresponds to the declared performance of point 6. The manufacturer according to point 3 is solely responsible for the production of this service.

Signed for and on behalf of the manufacturer by:

Dr. Thorsten Lauterbach (Research and development)

Aurich, February 12, 2021 (place and date of issue)

i.A. Gent (signature)