

# DECLARATION OF PERFORMANCE

According Annex III of the Regulation (EU) No 305/2011  
as amended by Delegated Regulation (EU) No 574/2014



## KÖSTER NB Elastic Grey

### Nr. P 240

- |    |  |   |
|----|--|---|
| 1. | Unique identification code of the product type:  | KÖSTER NB Elastic Grey<br>Nr. W 233<br>7294   |
| 2. | Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): | batch number: see packaging of the product  |
| 3. | Intended Use   | Liquid applied cement based waterproofing product with improved crack bridging capacity at low temperatures for use under ceramic and loose-laid tiles in interior and exterior areas<br>EN 14891 CM, O1P |
| 3. | Manufacturer:  | KÖSTER BAUCHEMIE AG<br>Dieselstraße 1 - 10<br>26607 Aurich  |
| 4. | Systems for evaluation and verification of constancy of performance:   | System 3  |
| 5. | Harmonized standard:   | EN 14891:2012   |
| 6. | Notified bodies:   | The notified body Institute MPA Braunschweig (NB 0761) has performed the determination of the product type (System 3) on the basis of type testing and issued   |

## 7. Declared performance:


Main features	Performance	Performance evaluation and verification system	Harmonized technical specification
Initial tensile adhesion strength	$\geq 0.5 \text{ N/mm}^2$	EN 14891:2012 System 3	
Tensile adhesion strength after water contact	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after heat ageing	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after freeze-thaw cycles	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with lime water	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with chlorinated water	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with chlorinated water	$\geq 0.75 \text{ mm}$		
Crack bridging ability at low temperatures (-5 °C)	$\geq 0.75 \text{ mm}$		
Waterproofing	Waterproof and $\leq 20 \text{ g}$ mass increase		

The performance of the above-mentioned product conforms to the declared performance. The declaration of performance is issued under the sole responsibility of the manufacturer identified above in accordance with Regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer:

Dr. Eike Kunst  
(Research and Development Export)

Aurich, 18.07.2025  
.....  
(Place and date of issue)

  
.....  
(Signature)