

DECLARATION OF PERFORMANCE

According Annex III of the Regulation (EU) No 305/2011
as amended by Delegated Regulation (EU) No 574/2014



KÖSTER NB Elastic Grey

Nr. P 240

- | | | |
|----|--|---|
| 1. | Unique identification code of the product type: | KÖSTER NB Elastic Grey
Nr. W 233
7294 |
| 2. | Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): | batch number: see packaging of the product |
| 3. | Intended Use | Liquid applied cement based waterproofing product with improved crack bridging capacity at low temperatures for use under ceramic and loose-laid tiles in interior and exterior areas
EN 14891 CM, O1P |
| 3. | Manufacturer: | KÖSTER BAUCHEMIE AG
Dieselstraße 1 - 10
26607 Aurich |
| 4. | Systems for evaluation and verification of constancy of performance: | System 3 |
| 5. | Harmonized standard: | EN 14891:2012 |
| 6. | Notified bodies: | The notified body Institute MPA Braunschweig (NB 0761) has performed the determination of the product type (System 3) on the basis of type testing and issued |



7. Declared performance:

Main features	Performance	Performance evaluation and verification system	Harmonized technical specification
Initial tensile adhesion strength	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after water contact	$\geq 0.5 \text{ N/mm}^2$	System 4 EN 14891:2012	
Tensile adhesion strength after heat ageing	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after freeze-thaw cycles	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with lime water	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with chlorinated water	$\geq 0.5 \text{ N/mm}^2$		
Tensile adhesion strength after standard conditions	$\geq 0.75 \text{ mm}$		
Crack bridging ability at low temperatures (-5 °C)	$\geq 0.75 \text{ mm}$		
Waterproofing	Waterproof and $\leq 20 \text{ g}$ mass increase		

The performance of the above-mentioned product conforms to the declared performance. The declaration of performance is issued under the sole responsibility of the manufacturer identified above in accordance with Regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer:

Dr. Eike Kunst
(Research and Development Export)

Aurich, 14.11.2025
.....
(Place and date of issue)


.....
(Signature)